

PennTex Alternator Application Guide for Bus OEM

2009-2010 Chevrolet

<u>ENGINE</u>	<u>CHASSIS</u>	<u>PENNTEX ALT. KIT</u>	<u>NOTES</u>
6.0L gas	GMT-610 cutaway chassis (C3500) (Express & Savana)	*PX-422V-2, 4, or 10 Rated at 220 amps max. output with 110 amps idle output at most low engine idles.	*Drop in fit in the single OEM alternator location **PX-422V-2 & 4 are used for special output post clock positioning to allow for special clearance needs when the alternator is relocated to a secondary A/C compressor bracket.
6.6L diesel	GMT-610 cutaway chassis (C3500) (Express & Savana)	*PX-422V-10 or **PX-422V-2 Rated at 220 amps max. output with 110 amps idle output at most low engine idles.	*Drop in fit in the single OEM alternator location **PX-422V-2 is used for a special 2:00 output post clocking to allow for special clearance needs when the alternator is relocated to a secondary A/C compressor bracket.
6.6L diesel	GMT-540 and 560 chassis (C4500 - 5500)	PX-422V-10 Rated at 220 amps max. output with 110 amps idle output at most low engine idles.	Will mount in both OEM alternator locations.
8.1L gas	GMT-540 & 560 chassis (C4500 - 5500)	PX-422V-10 Rated at 220 amps max. output with 110 amps idle output at most low engine idles.	Drop in fit in the OEM alternator location

PennTex Alternator Application Guide for Bus OEM

2009-2010 Ford

<u>ENGINE</u>	<u>CHASSIS</u>	<u>PENNTEx ALT. KIT</u>	<u>NOTES</u>
5.4L gas	E-350-450 E-series chassis	PX-220RC-A Rated at 200 amps max. output with 90 amps idle output at most low engine idles.	Used with vehicle chassis that have dual A/C compressors. (Max-A/C system) The second A/C compressor bracket is also the mounting location for the alternator.
5.4L gas	E-350-450 E-series chassis	PX-220RC-T Rated at 200 amps max. output with 90 amps idle output at most low engine idles.	Used with vehicle chassis that use only the OEM A/C compressor. (Tie-In System) The alternator mounting holes are 8mm and it will mount in the OEM alternator location.
6.0L Diesel	E-350/450 E-series chassis	PX-520TDM-6, 6C or 12 Rated at 230 amps max. output with 130 amps idle output at most low engine idles.	Fits in OEM alternator location with the use of a support bracket and belt change . Please contact PennTex with specific chassis info regarding this application and A/C configuration.
6.0L Diesel	E-350/450 E-series chassis	PX-525TDM-6, 6C or 12 Rated at 250 amps max. output with 125 amps idle output at most low engine idles.	Fits in OEM alternator location with the use of a support bracket and belt change . Please contact PennTex with specific chassis info regarding this application and A/C configuration.
6.8L v10 gas	E-350/450 E-series chassis	PX-520RDC Rated at 230 amps max. output with 130 amps idle output at most low engine idles.	Used with vehicle chassis that have dual A/C compressors. (Max-A/C system) The second A/C compressor bracket is also the mounting location for the alternator.
6.8L v10 gas	E-350/450 E-series chassis	PX-525RDC Rated at 250 amps max. output with 125 amps idle output at most low engine idles.	Used with vehicle chassis that have dual A/C compressors. (Max-A/C system) The second A/C compressor bracket is also the mounting location for the alternator.
6.8L v10 gas	E-350/450 E-series chassis With Tie-in A/C Systems (single OEM Compressor)	PX-520RDC or PX-525RDC Rated at 230 amps max. output with 130 amps idle output at most low engine idles.	For use on a vehicle chassis that will only have a single OEM A/C compressor and a tied-in rear condenser, the PX-2517-09 support bracket and belt kit must be utilized.



Application Guide for Alternator Kits

Sales Technical Support
Toll Free 1-877-590-7366
Sales Fax 1-817-590-0505
Tech Fax 1-817-590-0398

CATERPILLAR

Engine	Chassis	Years	PennTex Part #	Notes
3126 (C-7)	Freightliner FB-65 / FS-65	2001 - and up	PX-627SF or PX-627Q	J180 mount style or Quad Pad Mount. Replaces L/N 270 amp.
C12 / C13	Transit Bus and Motorcoach	2006 - and up	PX-833****	Upgrade air-cooled replacement for the belt-driven oil-cooled 50-DN.
****PX-833 series is a 28-volt, 330-amp air-cooled upgrade replacement for the oil-cooled 50-DN.				

CHEVROLET / GMC

Engine	Chassis	Years	PennTex Part #	Notes
5.3L Gas	Cadillac Escalade Limo	2002 - and up	PX-422V-10	Harness connection modification may be necessary on 2002 model.
5700 Vortec	G-Van Shuttle Bus	1997-98 (some 96)	PX-421V superceded to PX-422V-10	Harness modification necessary (Early 1996 models may require 96-inch belt).
5.7L Gas	Express & Savanna Vans	1999 - 2002	PX-420G-5	Uses PX-1128 K6 pulley.
6.0L Gas	Cadillac Escalade Limo	2003 - and up	PX-422V-10	Drop in fit in the OEM alternator location.
6.0L Gas	H-2 Humvee Limo	2003 - and up	PX-422V-10	Drop in fit in the OEM alternator location.
6.0L Gas	Suburban Limo	2003 - and up	PX-422V-10	Drop in fit in the OEM alternator location.
6.0L Gas (C3500 chassis)	Express & Savanna Vans	2003 - and up	PX-422V-10* or PX-422V-2/4**	Drop in fit in the OEM alternator location. (See footnotes * and ** below)
6.0L Gas	Tahoe and Yukon	2003 - and up	PX-422V-10	Drop in fit in the OEM alternator location.
6.5L Turbo Diesel	G-Van & Express / Savanna	1997- 02 (some 96)	PX-420G-5	Equipped with PX-1128 K6 pulley, May require a 102.62-inch belt on G-vans.
6.6L Diesel (C4500 chassis)	GMT-540 Shuttle Bus	2006 - and up	PX-422V-10	Drop in fit in the OEM alternator location.
6.6L Diesel (C5500 chassis)	GMT-560 Shuttle Bus	2006 - and up	PX-422V-10	Drop in fit in both OEM alternator locations. (See special note)
Special Note - Earlier 2003 to 2005 C4500 and C5500 chassis with 6.6L diesel engine will require harness connection modification.				
6.6L Diesel (C3500 chassis)	GMT-610 Shuttle Bus	2006 - and up	PX-422V-10* or PX-422V-2/4**	Drop in fit in the OEM alternator location. (See footnotes * and ** below)
7400 Vortec	G-Van & Express / Savanna	1997- 2000 (some 96)	PX-420G-5	Equipped with PX-1128 K6 pulley. Older models may require a 100.62-inch belt.
8.1L Gas (C4500 & C5500)	GMT-540 / 560 Shuttle Bus	2005 - and up	PX-422V-10	Drop in for the OEM alternator location. Earlier years require harness modification.
8.1L Gas	Suburban Limo	2003 - and up	PX-422V-10	Drop in fit in the OEM alternator location.
* PX-422V-10 is the standard OEM 10:00 output post position.				
** PX-422V-2 and PX-422V-4 are used when a special output post clocking is needed to allow for special clearance needs when the alternator is relocated to a secondary A/C compressor bracket.				

CUMMINS

Engine	Chassis	Years	PennTex Part #	Notes
6BT 5.9 Diesel	Misc. Shuttle & School	1995 - and up	PX-320S, PX-325S, PX-328S***	Fits standard large J180 mount. Use PX-1355 K8 pulley on PX-328S.
*** PX-320S is a 14-volt, 200-amp charging system, PX-325S is a 14-volt, 250-amp charging system, and PX-328S is a 14-volt, 285-amp charging system.				
Special note - several engine manufacturers have upgrade alternator mounting brackets to replace the factory equipped Delco 21si and 22si alternators with the higher output PX-3 series.				
ISB / ISC	Freightliner FB-65	2002 - and up	PX-627SF	Must have large J180 mount bracket. Use PX-1355 K8 pulley.
ISB / ISC	Thomas / Bluebird	Most model years	PX-627S and PX-635S	Fits standard large J180 mount. Use PX-1355 K8 pulley.
ISC / ISL / ISM	Transit Bus and Motorcoach	1998 - and up	PX-833****	Upgrade air-cooled replacement for the belt-driven oil-cooled 50-DN.
**** PX-833 series is a 28-volt, 330-amp air-cooled upgrade replacement for the oil-cooled 50-DN.				

DETROIT DIESEL

Engine	Chassis	Years	PennTex Part #	Notes
Series 40 / 50 / 60	Thomas / Bluebird	Most model years	PX-627S and PX-635S	Fits standard large J180 mount. Use PX-1355 K8 pulley.
Series 50 / 60	Transit Bus and Motorcoach	Most model years	PX-833****	Upgrade air-cooled replacement for the belt-driven oil-cooled 50-DN.
****PX-833 series is a 28-volt, 330-amp air-cooled upgrade replacement for the oil-cooled 50-DN.				



Application Guide for Alternator Kits

Sales Technical Support
Toll Free 1-877-590-7366
Sales Fax 1-817-590-0505
Tech Fax 1-817-590-0398

DODGE/CHRYSLER

Engine	Chassis	Years	PennTex Part #	Notes
360 Gas	Ram Van	1995-2003	PX-220P2D-5	Equipped with PX-1155 K7 pulley. Bracket kit PX-3600 required.
5.9L Diesel	Ram Pick-up Truck	Various years	PX-421-SMD	Equipped with PX-1155 K7 pulley. Must use PX-1199 Field Wire Resistor Kit.

FORD

Engine	Chassis	Years	PennTex Part #	Notes
4.6L Gas	Ford Police / Lincoln Limo	1996 - 2002	PX-220RL-5T	Equipped with PX-1353 K6 pulley and PX-1335 rear support bracket.
4.6L Gas	E-250 series	Late 2001 - 2008	PX-220R-5T	For single OEM A/C compressor and a tied in rear condenser. (Tie-in Systems)
5.4L v8 Gas	E-350 / 450 series	1997 - late 2001	PX-220R-5 or PX-220R-5T	Equipped with PX-1130 K8 pulley and PX-1258T rear support bracket.
5.4L v8 Gas	E-350 / 450 series	Late 2001 - 2008	PX-220R-5A (7/16" bolt holes)	Used with dual A/C compressors & mount bracket (Max-A/C sys.)-K6 pulley.
5.4L v8 Gas	E-350 / 450 series	2009 - 2010	PX-220RC-A (7/16" bolt holes)	Used with dual A/C compressors & mount bracket (Max-A/C sys.)-K6 pulley.
5.4L v8 Gas	E-350 / 450 series	Late 2001 - 2008	PX-220R-5T (8mm bolt holes)	Used w/single OEM A/C comp (Tie-in Syst.) - K6 pulley & PX-1258T rear brace.
5.4L v8 Gas	E-350 / 450 series	2009 - 2010	PX-220RC-T (8mm bolt holes)	Used w/single OEM A/C comp (Tie-in Syst.) - K6 pulley & PX-1258T rear brace.
5.4L v8 Gas	F-250 / 350 series	1998 - 2006	PX-220R-5T	1998-01 use PX-1130 K8 pulley - 2002-06 uses PX-1129 K6 pulley.
5.4L v8 Gas	F-250 / 350 series	2007 - 2010	PX-220RM-5T (8mm bolt holes)	Works with PCM monitored system. Equipped with PX-1129 K6 pulley.
6.0L Diesel	E-350 / 450 series	2004 - 2010 * (1)	PX-520TD6 and PX-525TD6	Must use with BSI alternator support bracket & belt kit # A1-0052 for Max-A/C sys.
6.0L Diesel	E-350 / 450 series	2004 - 2010 * (2)	PX-520TD6C and PX-525TD6C	Must use with Carrier bracket & belt kit PX-5806 for single A/C comp.& Tie-in sys.
6.0L Diesel	E-350 / 450 series	2004 - 2010 * (3)	PX-520TD12 and PX-525TD12	Must use with Carrier bracket & belt kit # 72-62035-02 for Max- A/C system.
6.0L Diesel	F-250 / 550 series	2003 - 2010 * (4)	PX-220TF-6.0L	F- series diesel truck chassis only.

*** 2009 Application note:** 2009 6.0L diesel applications require a PCM monitored style charging system. See part numbers referenced below or contact PennTex for additional application assistance.

(1) PX-520TDM6, PX-525TDM6 (2) PX-520TDM6C, PX-525TDM6C (3) PX-520TDM12, PX-525TDM12 (4) PX-220TFM-6.0L

6.8L v10 Gas	E-350 / 450 series	1997 - 2001	PX-520RD and PX-525RD	Equip. w/ PX-1130 K8 pulley. Special mounting bracketry required. (See footnote **)
6.8L v10 Gas	E-350 / 450 series	2002 - 2008	PX-520RD and PX-525RD	Equip. w/ PX-1129 K6 pulley. Special mounting bracketry required. (See footnote **)
6.8L v10 Gas	E-350 / 450 series	2009 - 2010	PX-520RDC and PX-525RDC	Equip. w/ PX-1129 K6 pulley. Special mounting bracketry required. (See footnote **)

**** For Max-A/C system chassis (two A/C compressors), the PX-5RD series usually mounts onto the second A/C compressor bracketry.**

**** For single A/C compressor chassis-use the following bracket kits: (1997-01) use **PX-2517-3** - (2002-07) use **PX-2517-4** - (2008) use **PX-2517-08** - (2009-2010) use **PX-2517-09**.**

6.8L v10 Gas	E-350 / 450 series	2002 - 2008	PX-220R-5 or PX-220R-5T	Only used when support bracketry for PX-5RD series is not available.
6.8L v10 Gas	E-350 / 450 series	2009 - 2010	PX-220RC-T	Only used when support bracketry for PX-5RD series is not available.
6.8L v10 Gas	F-250 / 550 series	1998 - 2006	PX-220R-5 or PX-220R-5T	1998-01 uses PX-1130 K8 pulley - 2002-06 uses PX-1129 K6 pulley.
6.8L v10 Gas	F-250 / 550 series	2007 - 2010	PX-220RM-5 or PX-220RM-5T	Works with PCM monitored system. Equipped with PX-1129 K6 pulley.
7.3L Diesel	E-350 series	1988 - Feb. 1992	PX-220P-5	Needs a special double groove pulley - 3-5/16"OD x 1/2" x 3/8" grooves.
7.3L Diesel	E-350 series	Mar. 1992 - 1994	PX-220T-5	1992 uses a K6 or K7 pulley; 93-94 uses a K8 pulley.
7.3L Diesel	E-350 / 450 series	1995 - 2003	PX-520TD / PX-627T/ PX-635T	The PX-5T uses PX-1130 K8 pulley; the PX-6T uses PX-1238 K8 pulley.
7.3L Diesel	F-250 / 450 series	1995 - 2003	PX-220TF or PX-520TFD	Equipped with PX-1130 K8 pulley.
7.5L 460 Gas	E-350 series	1988 - 1996	PX-220P-5	Equipped with PX-1129 K6 pulley. May require modifications to OEM bracket.
7.5L 460 Gas	E-350 series	1994 - 1996	PX-520PD	Equipped with PX-1129 K6 pulley. May require modifications to OEM bracket.



Sales Technical Support
Toll Free 1-877-590-7366
Sales Fax 1-817-590-0505
Tech Fax 1-817-590-0398

Application Guide for Alternator Kits

FREIGHTLINER

Engine	Chassis	Years	PennTex Part #	Notes
Caterpillar 3126 (C7)	FB-65, MB-45, MB-55	2001 - and up	PX-627SF or PX-627Q	J180 mount style or Quad Pad Mount. Replaces L/N 270 amp.
Cummins ISB / ISC	FB-65, MB-45, MB-55	2001 - and up	PX-627Q and PX-635Q	Quad pad mount for Cummins.
Mercedes 6.4L	FB-65, MB-45, MB-55	2001 - and up	PX-627SF	J180 mount style. Replaces L/N 270 amp.

INTERNATIONAL/NAVISTAR

Engine	Chassis	Years	PennTex Part #	Notes
T444E	3400, 3000RE, 3800	1994 - 2002	PX-320S, PX-325S, PX-328S*	Fits standard large J180 mount. Use PX-1355 K8 pulley. (See footnote*)
T444E	3400 / 3800	1995 - 2002	PX-627S and PX-635S	Fits standard large J180 mount. Use PX-1355 K8 pulley.
DT466	International / Bluebird	Most model years	PX-627S and PX-635S	Fits standard large J180 mount. Use PX-1355 K8 pulley.
7.6L Maxx-force D7	IC School Bus - RE300	2008 - and up	PX-627Q and PX-635Q	Fits standard large quad pad mount. Use PX-1355 K8 pulley.
T444E, DT-466, VT-365	3200, 3400, 3800 chassis	2003 - and up	PX-627S and PX-635S	Fits standard large J180 mount. Use PX-1355 K8 pulley.
Misc. Eng. w/Delco 21 / 22si	Misc. chassis	Most model years	PX-421JM**	Delco 21si and 22si replacement. Use PX-1131 K8 pulley on Cummins engine.
Misc. Eng. w/Delco pad mnt.	Misc. chassis	2003 - and up	PX-421PM**	Delco pad mount replacement. Use PA-4020 K8 pulley. (See footnote*)

* PX-320S is a 14-volt, 200-amp charging system, PX-325S is a 14-volt, 250-amp charging system, and PX-328S is a 14-volt, 285-amp charging system.

** Special note - several engine manufactures have upgrade alternator mounting brackets to replace the factory equipped Delco 21si and 22si alternators with the higher output PX-3 series.

ISUZU

Engine	Chassis	Years	PennTex Part #	Notes
6.0L Gas (GM)	NPR HD Series	2008 - 2010	PX-422V-10	Drop in fit in the OEM alternator location.

WORKHORSE CHASSIS

Engine	Chassis	Years	PennTex Part #	Notes
6.5L Diesel	Workhorse Worktruck	2002 - 2004	PX-422V	Harness plug modification may be necessary on some older models.
6.6L Diesel	Workhorse Worktruck	2005 - and up	PX-422V	Drop in fit in the OEM alternator location.
8.1L Gas	Workhorse Worktruck	2002 - 2004	PX-422V	Harness plug modification may be necessary on some older models.
8.1L Gas	Workhorse Worktruck	2005 - and up	PX-422V	Fits in OEM location with plug in harness.
Cummins ISB / ISC	Workhorse Bus Chassis with	2002 - and up	PX-627Q (275A)	Large frame four bolt Pad Mount style for Cummins.
	Quad Pad Mount alternators		PX-635Q (350A)	

For Batteryless 28-volt A/C applications the 140-amp (PX-614S) is available.

For normal 28-volt applications the 175-amp PX-317 series, 160-amp PX-616 series, and 190-amp PX-619 series alternators are also available.